## §72.20-35 Hospital space.

- (a) Each vessel which in the ordinary course of its trade makes voyages of more than 3 days duration between ports and which carries a crew of 12 or more, must be provided with a hospital space. This space must be situated with due regard to the comfort of the sick so that they may receive proper attention in all weathers.
- (b) The hospital must be suitably separated from other spaces and must be used for the care of the sick and for no other purpose.
- (c) The hospital must be fitted with berths in the ratio of 1 berth to every 12 members of the crew, or portion thereof, who are not berthed in single occupancy rooms, but the number of berths need not exceed 6.
- (d) The hospital must have a toilet, washbasin, and bathtub or shower conveniently situated. Other necessary suitable equipment such as a clothes locker, a table, and a seat must be provided.

## $\S72.20-40$ Other spaces.

Each vessel must have-

- (a) Sufficient facilities where the crew may wash and dry their own clothes, including at least 1 sink supplied with hot and cold fresh water;
  - (b) Recreation spaces; and
- (c) A space or spaces of adequate size on an open deck to which the crew has access when off duty.

## $\S72.20-45$ Lighting.

Each berth must have a light.

## $\S72.20-50$ Heating and cooling.

- (a) All manned spaces must be adequately heated and cooled in a manner suitable to the purpose of the space.
- (b) The heating and cooling system for accommodations must be capable of maintaining a temperature of 21 °C (70 °F) under normal operating conditions without curtailing ventilation.
- (c) Radiators and other heating apparatus must be so placed and shielded, where necessary, to avoid risk of fire, danger or discomfort to the occupants. Pipes leading to radiators or heating apparatus must be insulated where those pipes create a hazard to persons occupying the space.

#### § 72.20-55 Insect screens.

Provisions must be made to protect the crew quarters against the admission of insects.

# § 72.20-90 Vessels contracted for prior to November 19, 1952.

- (a) Vessels of 100 gross tons and over, contracted for prior to March 4, 1915, must meet the requirements of this paragraph.
- (1) Existing structure, arrangements, materials, and facilities, previously approved will be considered satisfactory so long as they are maintained in a suitable condition to the satisfaction of the Officer in Charge, Marine Inspection.
- (2) Minor repairs and alterations may be made to the same standard as the original construction provided that in no case will a greater departure from the standards of §§ 72.20–5 through 72.20–55 be permitted than presently exists.
- (b) Vessels of 100 gross tons and over, contracted for on or after March 4, 1915, but prior to January 1, 1941, must meet the following requirements:
- (1) Existing structure, arrangements, materials, and facilities, previously accepted or approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standard as the original construction.
- (2) Where reasonable and practicable, a minimum of 1 toilet, shower, and washbasin must be provided for each 10 members of the crew or fraction thereof.
- (3) Crew spaces must have a volume of at least 3.4 cubic meters (120 cubic feet) and a deck area of at least 1.5 square meters (16 square feet) for each person accommodated.
- (4) Each crewmember shall have a separate berth, and berths may not be placed more than 2 high.
- (5) Each vessel, which in the ordinary course of its trade makes a voyage of more than 3 days duration between ports and which carries a crew of 12 or more persons, must be provided with a suitable hospital space for the exclusive use of the sick or injured. Berths must be provided in the ratio of 1 berth for each 12 members of the crew or